

REQUEST TO EXIT STATIONS FOR MAGNETIC LOCKS AND ELECTRIC DOOR STRIKES

MODEL TS-10

- VANDAL RESISTANT .750 INCH DIA. BRASS NICKEL PLATED PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 4 AMP. @ 25 VDC OR 125 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- RED AND GREEN LEDS OPERATE ON 12 OR 24 VOLTS AC/DC
- SWITCH MOUNTED ON SINGLE GANG 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.5 INCHES
- SWITCH CONSTRUCTED TO MEET IP65 STANDARD, (DIRECT WATER SPRAY)
- UL APPROVED AND CSA CERTIFIED COMPONENTS



MODEL TS-11

- VANDAL RESISTANT .750 INCH DIA. BRASS NICKEL PLATED PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 4 AMP. @ 25 VDC OR 125 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- RED, GREEN LEDS OPERATE ON 12 OR 24 VDC, INDEPENDENTLY WIRED
- SWITCH MOUNTED ON 1.75 INCH 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.5 INCHES
- SWITCH CONSTRUCTED TO MEET IP65 STANDARD, (DIRECT WATER SPRAY)
- UL APPROVED AND CSA CERTIFIED



MODEL TS-12

- VANDAL RESISTANT .750 DIA. BRASS NICKEL PLATED PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 4 AMP. @ 25 VDC OR 125 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.5 INCHES
- SWITCH CONSTRUCTED TO MEET IP65 STANDARD, (DIRECT WATER SPRAY)
- UL APPROVED AND CSA CERTIFIED COMPONENTS



MODEL TS-13

- VANDAL RESISTANT .750 DIA. BRASS NICKEL PLATED PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 4 AMP. @ 25 VDC OR 125 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON 1.75 INCH 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.5 INCHES
- SWITCH CONSTRUCTED TO MEET IP65 STANDARD, (DIRECT WATER SPRAY)
- UL APPROVED AND CSA CERTIFIED COMPONENTS



MODEL TS-34

REMOTE AUDIO INDICATOR

- 85 dB PIEZO BUZZER
- 3 TO 28 VDC OPERATION, 20 MA. MAX.
- 5" COLOR CODED LEADS
- MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- AVAILABLE ON 1.75" 302 STAINLESS STEEL WALLPLATE



SPECIFY
MODEL TS-34N
FOR 1.75" WIDE 302 STAINLESS
STEEL WALLPLATE

MODEL EXP-1

EXPLOSION-PROOF REQUEST TO EXIT SWITCH

- CONFORMS TO CLASS I, DIVISION 1 & II, GROUP B, C & G, NEMA 7 & 8
- MOMENTARY ACTION SWITCH
- ONE NORMALLY OPEN AND ONE CLOSED CONTACT
- CONTACTS RATED 5 AMP. @ 35 VDC OR 120 VAC
- HEAVY CASTING WITH 2 INCH DIA. ALUMINUM PUSHBUTTON
- SIZE 4" W x 6.6" L x 4.5" H
- 1/2-14 NPT PIPE THREAD
- UL APPROVED AND CSA CERTIFIED



SPECIFY
MODEL EXP-2
FOR LATCHING CONTACTS