

DOOR CONTROL STATIONS

FOR MAGNETIC LOCKS AND ELECTRIC DOOR STRIKES

MODEL TS-18

UNDER COUNTER/DESK DOOR RELEASE WITH MOMENTARY PUSHBUTTON

- MOMENTARY PUSHBUTTON
- S.P.D.T. CONTACTS, RATED 4 AMP. @ 28 VDC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- PUSHBUTTON PROTECTED WITH 1 INCH DIAMETER GUARD RING
- BLACK PLASTIC BOX WITH TWO MOUNTING EARS
- ENCLOSURE SIZE 1" H x 1.5" W x 2" L



MODEL TS-20

UNDER COUNTER/DESK DOOR RELEASE WITH ALTERNATE ACTION PUSHBUTTON

- ALTERNATE ACTION PUSHBUTTON
- S.P.D.T. CONTACTS, RATED 4 AMP. @ 28 VDC
- SWITCHES TERMINATED WITH COLOR CODED LEADS
- PUSHBUTTON PROTECTED WITH 1 INCH DIAMETERS GUARD RING
- BLACK PLASTIC BOX WITH TWO MOUNTING EARS
- ENCLOSURE SIZE 1" H x 1.5" W x 2" L



MODEL TS-17

KEY CONTROLLED UNDER COUNTER/DESK DOOR RELEASE

OPERATION

DEPRESSING BUTTON WILL OPERATE THE SWITCH CONTACTS. PUSHBUTTON CAN BE LOCKED IN EITHER THE OPEN OR CLOSED POSITION BY USING THE KEY PROVIDED.

- ONE NORMALLY-OPEN AND ONE NORMALLY-CLOSED CONTACT
- CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SUPPLIED WITH TWO KEYS
- BLACK PLASTIC BOX WITH TWO MOUNTING EARS
- ENCLOSURE SIZE 1.5" H x 3" W x 3" L
- UL APPROVED AND CSA CERTIFIED COMPONENTS



MODEL TS-33

WALL MOUNTED KEY CONTROLLED DOOR RELEASE

OPERATION



DEPRESSING BUTTON WILL OPERATE THE SWITCH CONTACTS. PUSHBUTTON CAN BE LOCKED IN EITHER THE OPEN OR CLOSED POSITION BY USING THE KEY PROVIDED.

- ONE NORMALLY-OPEN AND ONE NORMALLY-CLOSED CONTACT
- CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC, SCREW TERMINALS
- SUPPLIED WITH TWO KEYS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- UL APPROVED AND CSA CERTIFIED COMPONENTS



CUSTOM PLATES DESIGNED TO SPECIFICATION

EXAMPLES OF CUSTOM PLATES THAT HAVE BEEN FABRICATED TO CUSTOMER'S REQUIREMENT



ALARM CONTROLS CORPORATION

"QUALITY SECURITY EQUIPMENT SINCE 1971"

19 BRANDYWINE DRIVE, P.O. BOX 280, DEER PARK, NEW YORK 11729

1 800 645-5538 631 586-4220 FAX 631 586-6500

EMAIL: INFO@ALARMCONTROLS.COM WWW.ALARMCONTROLS.COM