

# PUSHBUTTON CONTROL STATIONS FOR EMERGENCY / PANIC / DURESS

MODEL	SWITCH TYPE	OPTIONS
PBM	MOMENTARY	ILLUMINATED OPERATOR, GUARD RING LAMP VOLTAGES: 6, 12, 24 VDC OR 120 VAC
PBL	LATCHING	ILLUMINATED OPERATOR, GUARD RING LAMP VOLTAGES: 6, 12, 24 VDC OR 120 VAC
KR	LATCHING, KEY RESET	GUARD RING (ILLUMINATION N/A)

## ADDITIONAL OPTIONS

CUSTOM SILKSCREENING  
ANY COMBINATION OF SWITCHES  
A VARIETY OF PLATE FINISHES  
1.75" SLIMLINE PLATE  
MULTIPLE GANG PLATES

## ACCESSORIES

SURFACE MOUNT BOX W/ TAMPER SWITCHES  
(MODEL SMB-1)  
WALLPLATE RETAINER  
(MODEL WPR)  
TIMER TO EXTEND CONTACT "ON" TIME



## SPECIFICATIONS

CONTACT RATING: 10 @ 35 VDC OR  
120 VAC  
TEMP RANGE: -25C TO 70C  
SWITCH DEPTH: 2" STANDARD,  
2.5" ILLUMINATED  
WEATHER-PROOF: RATED TO IP65,  
NEMA TYPE 1, 2, 3, 3R, 4, 4X, 5, 1

## HOW TO ORDER

SELECT TYPE OF MODEL AND CONTACT ARRANGEMENT FROM CHART BELOW  
(UNLESS OTHERWISE SPECIFICIED ALL MODELS ARE MOUNTED ON 430 SERIES STAINLESS STEEL PLATES)

### STANDARD MODELS

### OPTIONS

MODEL	CONTACTS	PLATE	ILLUMINATION	GUARD RING
XXX	X	X	XX	XX
PBM	1 - N/O, NC	1 - 302 S.S.	L1 - 6 VDC	GR
PBL	2 - N/O, N/O	2 - WHITE	L2 - 12 VDC	
KR	3 - N/C, N/C	3 - IVORY	L3 - 24 VDC	
	4 - N/C	4 - RED	L4 - 120 VAC	
	5 - N/O	5 - 1.75" S.S.		
		6 - 1.75" RED		

EXAMPLE: PBL-1- 4-L2- GR

LATCHING PUSHBUTTON WITH ONE N/O AND ONE N/C  
CONTACT, RED PLATE, 12VDC ILLUMINATION, GUARD RING

# ALARM CONTROLS CORPORATION

"QUALITY SECURITY EQUIPMENT SINCE 1971"

19 BRANDYWINE DRIVE, P.O. BOX 280, DEER PARK, NEW YORK 11729

1 800 645-5538 631 586-4220 FAX 631 586-6500

EMAIL: [INFO@ALARMCONTROLS.COM](mailto:INFO@ALARMCONTROLS.COM) [WWW.ALARMCONTROLS.COM](http://WWW.ALARMCONTROLS.COM)