

# U.L. LISTED MAGNETIC LOCKS

## LIMITED LIFETIME WARRANTY

### MODEL 300S

300 POUND SINGLE LOCK



- 300 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 6-11/16" L x 1-1/2" H x 1-3/16" W
- ARMATURE SIZE: 5-1/2" L x 1-1/4" W x 7/16" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 250 MA. @ 12 VDC, 130 MA. @ 24 VDC
- INSTANT RELEASE, NO HYSTERESIS
- ALL NON-ALUMINUM PARTS PLATED
- IDEAL FOR CABINETS AND SHOWCASES
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

### MODEL 600S

600 POUND SINGLE LOCK



- 600 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 9-7/8" L x 1-11/16" H x 1" W
- ARMATURE SIZE: 7-1/4" L x 1-7/16" W x 5/8" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- INSTANT RELEASE, NO HYSTERESIS
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- E-Z MOUNTING SYSTEM, NO SPECIAL TOOLS REQUIRED REDUCES INSTALLATION TIME.
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

### MODEL 600D

600 POUND DOUBLE LOCK



- 600 POUND MINIMUM HOLDING FORCE PER LOCK
- MAGNET SIZE: 19-3/4" L x 1-7/8" H x 1" W
- ARMATURE SIZE: 7-1/4" L x 1-7/16" W x 5/8" D EACH
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC EACH LOCK
- INSTANT RELEASE, NO HYSTERESIS
- ALL NON-ALUMINUM PARTS PLATED
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

### MODEL 600L

600 POUND SINGLE LOCK WITH STATUS LED



- 600 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 9-7/8" L x 1-11/16" H x 1" W
- ARMATURE SIZE: 5-1/2" L x 1-1/4" W x 7/16" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- GREEN STATUS LED
- ALL NON-ALUMINUM PARTS PLATED
- INSTANT RELEASE, NO HYSTERESIS
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

### MODEL 600LB

600 POUND SINGLE LOCK W/LED & BOND SENSOR



- 600 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 9-7/8" L x 1-11/16" H x 1" W
- ARMATURE SIZE: 7-1/4" L x 1-7/16" W x 5/8" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- INSTANT RELEASE, NO HYSTERESIS
- BI-COLORED STATUS LED, S.P.D.T. 3A. RELAY CONTACTS
- SIGNALS A POWERED AND SECURELY SEALED LOCK
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

### MODEL 600WP

600 POUND WEATHER-PROOF GATE LOCK



- 600 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 9-7/8" L x 1-11/16" H x 1" W
- ARMATURE SIZE: 7-1/4" L x 1-7/16" W x 5/8" D
- 12 OR 24 VOLTS DC OPERATION
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- 10" COLOR CODED WIRE LEADS IN PLASTIC JACKET
- INSTANT RELEASE, NO HYSTERESIS
- COMPLETELY SEALED IN STAINLESS STEEL CASE
- IDEAL FOR SLIDING OR SWINGING GATES
- ALL METAL PARTS ARE PLATED TO RESIST CORROSION