

U.L. LISTED MAGNETIC LOCKS

LIMITED LIFETIME WARRANTY

MODEL 1200S 1200 POUND SINGLE LOCK



- 1200 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 10-1/2" L x 2-7/8" H x 1-1/2" W
- ARMATURE SIZE: 7-3/8" L x 2-3/8" W x 9/16" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- INSTANT RELEASE, NO HYSTERESIS
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- E-Z MOUNTING SYSTEM, NO SPECIAL TOOLS REQUIRED REDUCES INSTALLATION TIME.
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

MODEL 1200D 1200 POUND DOUBLE LOCK



- 1200 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 21" L x 2-7/8" H x 1-1/2" W
- ARMATURE SIZE: 7-1/2" L x 2-3/8" W x 5/8" D EACH
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC EACH MAGNET
- INSTANT RELEASE, NO HYSTERESIS
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- E-Z MOUNTING SYSTEM, NO SPECIAL TOOLS REQUIRED REDUCES INSTALLATION TIME.
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

MODEL 1200L 1200 POUND SINGLE LOCK WITH STATUS LED



- 1200 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 10-1/2" L x 2-7/8" H x 1-1/2" W
- ARMATURE SIZE: 7-3/8" L x 2-3/8" W x 9/16" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- GREEN STATUS LED
- ALL NON-ALUMINUM PARTS PLATED
- INSTANT RELEASE, NO HYSTERESIS
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

MODEL 1200LB 1200 POUND SINGLE LOCK W/LED & BOND SENSOR



- 1200 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 10-1/2" L x 2-7/8" H x 1-1/2" W
- ARMATURE SIZE: 7-3/8" L x 2-3/8" W x 9/16" D
- 12 OR 24 VOLTS DC, JUMPER SELECTABLE
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- INSTANT RELEASE, NO HYSTERESIS
- BI-COLORED STATUS LED, S.P.D.T. 3A. RELAY CONTACTS
- SIGNALS A POWERED AND SECURELY SEALED LOCK
- CAN BE USED WITH ANY ACCESS CONTROL SYSTEM
- CLEAR ANODIZED US 28 FINISH STANDARD, DURONIC US 40 FINISH AVAILABLE.

MODEL 1200WP 1200 POUND WEATHER-PROOF GATE LOCK



- 1200 POUND MINIMUM HOLDING FORCE
- MAGNET SIZE: 9" L x 2-5/8" H x 1-5/8" W
- ARMATURE SIZE: 7-1/2" L x 2-3/8" W x 9/16" D
- 12 OR 24 VOLTS DC OPERATION
- 400 MA. @ 12 VDC, 200 MA. @ 24 VDC
- 10" COLOR CODED WIRE LEADS IN PLASTIC JACKET
- FITTED WITH 1/2" I.D. AND 3/4" O.D. CONDUIT FITTING
- COMPLETELY SEALED IN STAINLESS STEEL CASE
- IDEAL FOR SLIDING AND SWINGING GATES
- ALL METAL PARTS ARE PLATED TO RESIST CORROSION

ARMORED DOOR LOOPS FOR ACCESS CONTROL DEVICES

MODEL DL-1



- 18 INCHES LONG
- .250 I.D. STEEL JACKET RESISTS ABRASION AND DAMAGE
- PLASTIC END CAPS
- MOUNTING HARDWARE INCLUDED
- CUSTOM LENGTHS AVAILABLE

MODEL DL-2



- 18 INCHES LONG
- .375 I.D. STEEL JACKET RESISTS ABRASION AND DAMAGE
- HEAVY DUTY DIE CAST END CAPS
- MOUNTING HARDWARE INCLUDED
- CUSTOM LENGTHS AVAILABLE