

ACCESSORIES FOR REMOTE PLATES

SURFACE MOUNT BOXES MODEL SMB-1

STEEL BEIGE COLOR BOX FOR SINGLE GANG PLATES, WITH FRONT AND REAR NORMALLY-OPEN TAMPER SWITCHES, CONTACTS RATED .75 A @ 125 V



MODEL SMB-1A
NORMALLY- CLOSED TAMPER SWITCHES

PUSHBUTTONS

MODEL K-5

NORMALLY-CLOSED, MOMENTARY SWITCH WITH BLACK BUTTON CONTACTS RATED .75 A @ 125 V

MODEL K-13

NORMALLY- OPEN, RED BUTTON

MODEL 450

WHITE FLUSH MOUNT N/O PUSH-BUTTON CONTACTS RATED .5 A


MODEL FA-200

D.P.D.T. ALTERNATE ACTION PUSH-BUTTON, CONTACTS RATED 2 A INDICATOR CHANGES FROM BLACK TO ORANGE



MODEL 426 BOX

GALVANIZED STEEL, NARROW RECESSED BOX FOR USE IN HOLLOW WALLS, SECURELY FASTENS NARROW REMOTE PLATES TO HOLLOW WALLS.



IDEAL FOR USE WITH RP-1, RP-1M, RP-3, RP-3M, RP-24, RP-25

ELECTRONIC BUZZERS

MODEL PA-100

PIEZO BUZZER, MOUNTS IN .75 DIA. HOLE, SOUND LEVEL 85 db @ 3 FT, OPERATING VOLTAGE 4 - 28 VDC

MODEL SC628

SONALERT, MOUNTS IN 1.125 DIA. HOLE, SOUND LEVEL 85 db @ 3 FT, OPERATING VOLTAGE 6 - 28 VDC,


MODEL LA32

PULSING BUZZER, MOUNTS IN .625 DIA. HOLE, ADJUSTABLE PULSE RATE FROM STEADY TO 600 PULSES PER MINUTE OPERATING VOLTAGE 12 - 24V AC/DC



MODEL 30203 BOX

DIE CAST SURFACE MOUNT BOX FOR USE WITH ALL SINGLE GANG PLATES, THREE 1/2" I.P.S. HOLES, SUITABLE FOR WET LOCATIONS




FOR USE WITH MODEL WP- 4, WP- 6 WEATHER-PROOF REMOTE PLATES

WEATHER-PROOF COVER

MODEL WPC

SINGLE GANG METAL WEATHER-PROOF COVER, FOR USE WITH 30203 WEATHER-PROOF BACK BOX



WALLPLATE RETAINERS

SECURELY FASTENS REMOTE PLATES TO HOLLOW WALLS

MODEL WPR

FOR SINGLE GANG PLATES

MODEL WPR-2

FOR DOUBLE GANG PLATES



TAMPER SWITCHES

MODEL TB-1

NORMALLY - OPEN SWITCH FOR C/C

MODEL TB-2

NORMALLY - CLOSED SWITCH FOR O/C



KEYSWITCHES

MODEL KA-107

MOMENTARY ACE LOCK, TWO ROUND KEYS KEYED DIFFERENTLY

MODEL KA-108

ON-OFF ACE LOCK, TWO ROUND KEYS KEYED DIFFERENTLY

MODEL KA-109

ON-OFF, TWO SINGLE BITTED FLAT KEYS, KEYED DIFFERENTLY

MODEL KA-110

MOMENTARY, TWO SINGLE BITTED FLAT KEYS, KEYED DIFFERENTLY

FOR KEYED ALIKE KEYSWITCHES ADD SUFFIX "A" TO PART NUMBER

