


KR Series

Latching Panic Stations with Key Reset



Single gang panic station with latching key reset. Once activated the push button automatically latches, requiring the use of a key to reset. Ideal for applications requiring a personal response to an alarm condition. Choice of contact configurations ensures compatibility with most systems.

Features

Standard Features

- Single gang stainless steel wall plate, weather resistant to IP40 standards
- 1-1/2" red mushroom button
- Plate screened "EMERGENCY PUSH FOR HELP" to quickly call for assistance
- Alternate action switch

Options

- Plates: multiple finishes and widths available, specify when ordering
- **KR-1KEY** Replacement key

Specifications

Certifications & Listings

- Conforms to IP40

Electrical

- Available in any combination of N/O and/or N/C contact pairs. See table below.
- Contacts rated 10A at 35 VDC or 120 VAC
- Switch connection via screw terminals
- Switch depth behind plate: 2"

Operating Temperature

- -13F to +158 F (-25 to 70 C)

How To Order

MODEL	CONTACTS	PLATE	GUARD RING
KR	1	4	GR
KR Latching Key Reset	1 - One N/O pair and one N/C pair	1 - 302 Stainless Steel	GR Guard Ring
	2 - 2 N/O pairs	2 - White	LUC Lift Up Cover
	3 - 2 N/C pairs	3 - Ivory	(blank) NONE
	4 - 1 N/C pair	4 - Red	
	5 - 1 N/O pair	5 - 1-3/4" Stainless	
		6 - 1-3/4" Red	