

PBL Series

Latching Panic Stations



Single gang panic station with latching push button switch that remains active or inactive until actuated again. Choice of contact configurations ensures compatibility with most systems.

Features

Standard Features

- Single gang stainless steel wall plate, weather resistant to IP65 standards
- 1-1/2" red mushroom button
- Plate screened "EMERGENCY PUSH FOR HELP" to quickly call for assistance
- Alternate action switch

Options

- Plate: multiple finishes and widths available, specify when ordering
- Illumination: long life LED in 6V, 12V, 24V, 120V, specify when ordering
- **GR** Guard Ring
- **LUC** Lift up cover

Specifications

Certifications & Listings

- Conforms to IP65

Electrical

- Available in any combination of N/O and/or N/C contact pairs. See table below.
- Contacts rated 10A at 5 VDC or 120 VAC
- Switch connection via screw terminals
- Switch depth behind plate: 2-1/2"

Operating Temperature

- -13F to +158F (-25 to 70 C)

How To Order

| MODEL | CONTACTS | PLATE | ILLUMINATION | GUARD RING |
|-----------------------------|-----------------------------------|-------------------------|--------------|-------------------|
| PBL | 1 | 4 | L2 | GR |
| PBL Latching Operator | 1 - One N/O pair and one N/C pair | 1 - 302 Stainless Steel | L1 - 6VDC | GR Guard Ring |
| | 2 - 2 N/O pairs | 2 - White | L2 - 12VDC | LUC Lift Up Cover |
| | 3 - 2 N/C pairs | 3 - Ivory | L3 - 24VDC | (blank) NONE |
| | 4 - 1 N/C pair | 4 - Red | L4 - 120VAC | |
| | 5 - 1 N/O pair | 5 - 1-3/4" Stainless | | |
| | | 6 - 1-3/4" Red | | |